



Lowest Price. Extreme Precision. Premier Performance.

TECHNICAL DATA SHEET

PalmaOil 100 GO

DESCRIPTION:

PalmaOil 100 GO is a premium extreme pressure gear lubricant designed to provide excellent load carrying capacity, oxidative stability, corrosion protection, and water tolerance. It is formulated to meet the following typical properties.

TYPICAL SPECIFICATIONS:

ISO VISCOSITY GRADE	100
API GRAVITY	29.3
FLASH POINT OC (MIN.)	218
POUR POINT OC (MAX.)	-20
COPPER CORROSION	PASS
STEEL CORROSION (SYN SEA WATER)	PASS
EXTREME PRESSURE PROPERTIES	
TIMKEN OK LOAD, LB.	70
FOUR BALL; LWI/WELD LOAD KGF	50.7/250
ANTIWEAR PROPERTIES 4-BALL WEAR SCAR DIAM., MM	0.24
FZG PASSING STAGE	12
OXIDATION STABILITY, VISCOSITY INCREASE	0.9%
WATER SEPARABILITY (40/40/0 (15))	PASS

BENEFITS:

- Excellent load carrying
- Oxidation resistance
- Corrosion protection
- Water tolerance



CONTACT US TODAY:

PH: 317.914.2634 | PalmaryAmerica.com

1880 Northwood Plaza Dr | Suite 350 | Franklin, IN 46131

